



# ACUNTO WOOD-FIRED VESUVIO 120

SERIES: ACUNTO NAPOLI OVENS



Standard Acunto Vesuvio 120 Model, shipped from Acunto factory, with removable legs

JOB NAME: \_\_\_\_\_

REFERENCE INVOICE #: \_\_\_\_\_

LEGS:  REMOVABLE (Can be painted any color) \_\_\_\_\_

CUSTOM TILE:  YES  NO \_\_\_\_\_

CUSTOM TILE DOCUMENT #: \_\_\_\_\_

CUSTOM LETTERING ON OVEN:  YES  NO \_\_\_\_\_

PRINT LETTERING: \_\_\_\_\_

NOTES: \_\_\_\_\_

- Model #120 ships with a complementary Carrara Marble counter-top.
- Acunto Ovens are fully cured at the Forza Forni facility before delivery.
- Gas-fired ovens must be special-ordered from Italy and require additional lead time.



BAKING SURFACE	OVEN OPENING	EXTERNAL WIDTH	EXTERNAL DEPTH

## FEATURES

The Acunto Vesuvio 120 oven is a hand-built Neapolitan brick oven which features a cast steel door opening 17" wide by 8.75" high. The refractory baking floor diameter is 31 1/2", lined with hand-made clay bricks to form a dome. An internal steel and cement structure reinforces the dome and shapes the oven base. A proprietary mixture of Neapolitan sand, volcanic rock and clay form a thick insulation, ensuring heat retention.

The oven is finished with red and white quartz paint and white Carrara marble countertops - the painted surfaces are prepared for tiling. The oven may be installed with a choice of permanent welded steel legs, removable steel legs, or placed on an existing structure without factory provided legs. Information about the addition of gas burners, custom tiling, or leg options can be found online at [www.forzaforni.com](http://www.forzaforni.com).

## THE ORIGINAL NEAPOLITAN OVEN

Over 125 years of artisan oven-building experience go into each Acunto Neapolitan brick oven. Endorsed by both the *Vera Pizza Napoletana Association* and the *Neapolitan Association of Pizzaioli*, it is the oven of choice for authentic Neapolitan pizza.

## OVEN PRODUCTION

**12" PIZZA CAPACITY:** 6 - 7 PIZZAS

**RECOMMENDED BAKING TIME:** 90 - 120 SECONDS

**RECOMMENDED OVEN FLOOR**

**TEMPERATURE RANGE:** 750°F - 900°F

**DAILY PREHEAT TIME:** 1 HOUR

## CUSTOM TILE & LETTERING AVAILABLE



1-year warranty on oven parts

**FORZA FORNI**  
601 N Main St, Brewster, NY 10509  
Email: [info@forzaforni.com](mailto:info@forzaforni.com)  
[www.forzaforni.com](http://www.forzaforni.com)

**844-OVEN-INC (844-683-6462)**  
Toll-free in USA  
(Hablamos Español,  
Falamos Português)

Listed to: UL 2162, NSF-4  
Commercial Wood-Fired  
Baking Ovens - Refractory Type;  
File#: MH48941



DOC#: GAV120-0118-1

REVISED WINTER 2018. As products continue to improve, spec sheets may change without notice. Please call Forza Forni for the latest specification sheet and for further details.

MADE IN ITALY



# ACUNTO WOOD-FIRED VESUVIO 120

SERIES: ACUNTO NAPOLI OVENS

## LEGS

### Removable:

10" x 10" footprint per leg



Total height: 33.5" (850 mm) for both fixed and removable legs

We make every effort to provide accurate information regarding manufacturer's reported dimension information. Please note that due to the artisan nature of the manufacturing process, from time to time, product sizing and ship weight may vary slightly.

## CLEARANCES

Minimum clearance of the oven to combustible materials are as follows:


**Top: 18" (457 mm)**

**Back & Sides: 1" (25 mm)**

- Maintain required air space clearance between oven and combustible enclosure.
- Do not fill required air space with insulation or other materials.
- Non-combustible flooring must extend out at least 36" from oven opening and at least 30" to each side of the opening.

## VENTILATION REQUIREMENTS

Direct connection as a natural draft, grease-rated chimney system per NFPA 96 and UL 2162 is recommended. If the duct run exceeds 20 feet or incorporates a 90° elbow, a UL 705 & UL 762 listed rooftop exhaust fan shall be installed to ensure adequate pressure within the duct. A Listed Type 1 exhaust hood, or one constructed in accordance with all relevant local and national codes (NFPA 96), may also be installed above the oven in instances where a natural/power draft chimney system is otherwise impossible. See "Ventilation Document - Acunto" for details.



FLUE COLLAR  
CONNECTION  
DIAMETER  
(INTERNAL)

Operational airflow: 200 CFM

Static Pressure at Flue Collar:

0.05 in H<sub>2</sub>O

1-year warranty on oven parts

FORZA FORNI  
601 N Main St, Brewster, NY 10509  
Email: info@forzaforni.com  
www.forzaforni.com

844-OVEN-INC (844-683-6462)  
Toll-free in USA  
(Hablamos Español,  
Falamos Português)

Listed to: UL 2162, NSF-4  
Commercial Wood-Fired  
Baking Ovens - Refractory Type;  
File#: MH48941



DOC#: GAV120-0118-1

REVISED WINTER 2018. As products continue to improve, spec sheets may change without notice. Please call Forza Forni for the latest specification sheet and for further details.

MADE IN ITALY